I' GRADE STOCK

KEY FEATURES


- Round Column
- 6" x 8' 24" x 24'
- Colonial or Classical Styles

Courtesy of Renovation Style Magazine

- Plain or Fluted
- Tapered or Non-Tapered
- Precise Detailed **Proportions**
- One Year Limited Warranty
- Load Bearing
- Large Selection of **Decorative Capitals**

Dixie-Pacific offers Paint Grade Select Softwoods Stock Wood Columns in Colonial or Classical styles (plain or fluted). The Colonial Style has a gradual taper and double bead. The Classical Style has an architectural taper (bottom 1/3 is non-tapered; top 2/3 is tapered) and classical bead styling. The overall length of our wood columns includes cap, shaft and base/plinth. All columns can be custom ordered with a variety of special order options: splitting, splining

for reassembly, priming, asphaltum (interior coating), custom shaft lengths, and custom flute lengths. Standard Tuscan Caps and Roman Doric Base/Plinths are manufactured from high-density polyurethane. Wood capitals and base/plinths are available for interior use. A complete line of Decorative Capitals perfectly complements all Paint Grade Stock Wood Columns.



PAIN	T GRA	DE STO	OCK	WOOD									
	l _				I _		- 1	_	-	 	 	l	

Column Dia.	Bottom Dia.	Top Dia.	Plir	ıth	Base Mold	Squ Ca	are p	Round Cap	Colonial Bead	Classical Bead	Flute Width	Top Flute	Bottom Flute	Load Bearing Capacity
	A	В	С	D	E	F	G	Ĥ	K	K	L	M	N	(lbs.)
6	5 ½	4 ¾	8	1 1/4	1 ½	7 ½	1 1/4	1 1/8	1 %	1 %	3/4	3 ½	10 ¾	4,000
8	7 1/4	6 1/4	9 %	1 1/4	1 ½	9 ½	1 1/4	1 1/8	1 %	1 %	15/16	3 ½	10 ¾	6,000
10	9 1/4	8	11 %	1 1/4	1 ½	9 ½	1 1/4	1 1/8	1 %	1 %	15/16	3 ½	10 ¾	7,000
12	11 ¼	9 1/4	13 ¾	1 1/4	1 ½	12	1 1/4	1 1/8	1 %	1 %	15/16	3 ½	10 ¾	8,000
14	13 %	12	16 ½	1 %	2 1/8	14 ½	2	1 %	1 %	1 %	1 1/8	2 ¾	5	14,000
16	15 %	13 ½	18 ¾	2	2 ½	16	2 %	1 %	1 %	1 %	1 1/4	2 3/4	5	16,000
18	17 %	15	22 1/8	2 ¾	3 ½	18 ¾	2 %	2 1/4	1 %	1 %	1 ½	2 ¾	5	16,000
20	19 %	17	24 1/8	2 ¾	3 ½	20 %	3 1/8	2 ½	1 %	1 %	1 %	2 ¾	5	17,000
22	21 %	18 ½	29 ¾	5 1/4	6 ¾	26 ½	3 ¾	2 ½	1 %	1 %	1 ¾	2 3/4	5	20,000
24	23 %	20	32 ½	5 ¾	7 ½	28 ¾	4 1/8	2 ¾	1 %	1 %	1 %	2 3/4	5	22.000

The overall length of our Paint Grade Stock Wood Column includes the Tiscan Cap, Shaft and Roman Doric Base/Plinth.
 Allowable wood stress in compression parallel to grain is 800 PSI.
 Allowable loads are axial loads with no moments.

18 ½

- Load bearing capacity is dependant on the concentric loading of the columns.
 2nd story balconies should not be attached directly to the side of any column, contact Dixie-Pacific for recommendations.

ı	COLUMINS TO SURROUND STRUCTURAL SUPPORTS											
	Bottom Diameter (inches)	Inside Top Diameter (inches)	Largest Round (inches)	Largest Square (inches)	Stave Thickness After Turning Colonial/Classical							
	6	2 %	2 1/4	N/A	1 %	N-4						
	8	3 ¾	3 ½	N/A	1 1/4	Notes: • These						
	10	5 ½	5	3 ½	1 1/4	dimensions						
	12	6 %	6 ½	4 ½	1 %	allow for saw kerf as columns are						
	14	9	8 ½	6	1 %							
	16	10 ¾	10 ¼	7 ½	1 %	split.						
	18	12 ¼	11 ½	8 ½	1 %	Split columns						
	20	14 ¼	13 ¾	9 ½	1 ½	are non-load						
	22	15 ¾	15 1/4	10 ½	1 ½	bearing.						



Decorative Capitals are available. See pages 12 & 13.

Colonial Column Plain Shaft

PAINT GRADE STOCK WOOD COLUMNS Page 15